VIDYABHARATI
Vidyabharati International Interdisciplinary Research Journal
ISSN 2319-4979

Gravity Battery-Based Green Energy Storage Systems Architectural Concepts, Challenges, and Commercial Integration

Naresh Kumar
Department of Commerce, GDC Sandhole, District Mandi, Himachal Pradesh, India
atalaarya@gmail.com

Abstract
Gravity Battery Energy Storage Systems (GBESS) store electrical energy by using it to raise water or a solid mass and later recover part of that energy as electricity. The main physical principle is gravitational potential energy, expressed as $E = mgh$, where m is the mass, g is gravitational acceleration, and h is the vertical distance through which the mass is moved. During charging, electricity powers pumps, motors, winches, or other lifting equipment. During discharge, the controlled descent of water or a solid mass drives a turbine or motor-generator system. Because no conversion process is perfectly efficient, the electrical energy recovered is lower than the energy used to charge the system. This paper discusses the working principle, main components, and architectural options of gravity storage. It distinguishes pumped-storage hydropower (PSH), an established form of large-scale storage, from solid-gravity systems that use weights, towers, shafts, slopes, rail arrangements, or other mechanical designs. It also considers how gravity storage may be paired with wind and solar generation, and reviews its potential benefits, engineering challenges, environmental effects, and safety requirements. A commerce and business analysis connects the technology with capital expenditure (CAPEX), operating expenditure (OPEX), energy arbitrage, peak shaving, value stacking, project life, and financial evaluation. The paper explains how net present value (NPV), internal rate of return (IRR), payback period, and levelized cost of storage (LCOS) may support project appraisal. It concludes that gravity storage may be useful for particular stationary applications, but its feasibility depends on site characteristics, design performance, construction and maintenance costs, electricity-market rules, financing, and competition with other storage options. Pumped hydro is mature; many solid-gravity designs still need further operating evidence and commercial demonstration.

Keywords: *Gravity battery; gravity energy storage; solid-gravity energy storage; pumped-storage hydropower; renewable energy; wind energy; solar energy; CAPEX; OPEX; energy arbitrage; value stacking*

1. Introduction

Electricity demand changes throughout the day, while generation from wind and solar resources varies with weather, season, and time. A solar plant, for example, may generate its greatest output during daylight hours, even though a local system's highest demand may occur later in the evening. Wind generation can rise or fall according to wind conditions. When electricity is generated at a time when it cannot be used or transmitted economically, some available renewable generation may be curtailed.

Energy storage helps address this timing difference. It can absorb electricity when supply is high or demand is low and return electricity later. Gravity storage is one possible method. Instead of storing energy in chemical cells, it uses electricity to move water or a solid mass to a higher elevation. The raised material holds gravitational potential energy. When electricity is needed, the material is lowered in a controlled way and the system converts a portion of its stored energy back into electrical output.

The basic principle is straightforward, but a commercial project requires more than a heavy object and a height difference. It needs an appropriate site, structural support, lifting or pumping equipment, controls, protection systems, electrical conversion equipment, and a viable connection to the grid or a customer's facility. The project must also meet safety, environmental, and regulatory requirements. Its overall value depends not only on how much energy it can store, but also on its power rating, discharge duration, efficiency, operating schedule, lifetime costs, and available revenue.

Gravity storage includes different technologies that should not be treated as identical. Pumped-storage hydropower uses water and reservoirs. Solid-gravity designs use mechanical arrangements to move solid masses. Pumped hydro has an established history of operation, while many solid-gravity designs are still developing. This distinction matters when comparing performance, reliability, cost, commercial maturity, and project risk.

This paper therefore considers gravity storage both as an energy technology and as a potential infrastructure business. It introduces the physical and architectural principles, examines possible

roles in renewable-energy systems, and explains why technical feasibility must be assessed together with commercial feasibility.

Research Gap

The available discussion of gravity storage contains several areas where clearer, application-oriented analysis is useful:

- Different maturity levels: Pumped-storage hydropower has more operating history than many solid-gravity designs. Evidence from one type should not automatically be applied to another.
- Technical and commercial separation: A design may appear workable in engineering terms but still lack a convincing business case. Technical performance and revenue opportunities need to be assessed together.
- Architectural diversity: Towers, shafts, mine-based systems, slopes, rail concepts, and water reservoirs have different structural, geographic, and operational needs.
- Revenue uncertainty: A project may not be viable if it depends only on buying electricity cheaply and selling it at a higher price. Several services may be needed, depending on market rules.
- Site-specific impacts: Water availability, geology, land use, existing infrastructure, grid access, and local acceptance vary by location.
- Need for accessible analysis: Students, communities, and early-stage developers need explanations that connect the physical process to project economics and practical limitations.
- Indian application: More project-specific study is needed to determine where gravity storage could complement India's changing electricity mix, rather than assuming that one design will suit all regions.

Research Objective

The objectives of this paper are:

To explain the working principle of a Gravity Battery Energy Storage System.

To describe the components that may be used in gravity-storage projects.

To distinguish pumped-storage hydropower from solid-gravity storage.

To explain how gravity storage could be paired with wind and solar generation.

To examine the potential benefits and limitations of the technology.

To identify architectural, mechanical, electrical, safety, and environmental challenges.

To connect storage technology with CAPEX, OPEX, energy arbitrage, peak shaving, and value stacking.

To explain how NPV, IRR, payback period, and LCOS can be used in project evaluation.

To discuss possible opportunities and conditions for gravity-storage projects in India.

Research Questions

How does a gravity battery store and release electricity?

What components are necessary for the main types of gravity-storage systems?

How do water-based and solid-mass designs differ?

In what ways could gravity storage support variable wind and solar generation?

What engineering, environmental, and safety challenges must be addressed?

Which business models and financial measures may be relevant to a gravity-storage project?

What conditions would influence the feasibility of a project in India?

Research Propositions

This paper examines the following propositions:

Gravity storage may be useful for stationary energy-storage applications, including some applications that require energy to be shifted over longer periods.

Pumped-storage hydropower is a mature form of gravity storage, while solid-gravity systems represent a varied group of developing designs.

Combining multiple services may improve project value, if market rules and system operation allow those services to be delivered.

Long-lived civil infrastructure may reduce the need for frequent replacement of an entire system, but equipment still requires inspection, maintenance, and possible replacement.

Returns depend on project-specific factors, including construction cost, charging and discharging prices, utilization, financing, efficiency, market access, and permitting.
The environmental performance of a gravity-storage project depends on its full lifecycle, not merely on whether it uses chemical battery cells.

2. Literature Review

Amorim et al. (2026) provide a systematic review highlighting that Gravity Energy Storage (GES) has emerged as a critical technological pathway for achieving medium- to long-duration energy storage. Their work emphasizes the growing importance of GES in the context of power systems increasingly dominated by renewable energy sources, underscoring its role in grid stabilization and reliability.
Kavoosi et al. (2025) contribute a comprehensive overview of Solid Gravity Energy Storage (SGES) technologies. Their research serves as a key reference for understanding the potential of SGES in large-scale energy storage applications. By evaluating various system architectures, they highlight the viability of solid mass mechanisms to address future energy capacity demands.
Ji et al. (2025) focus on the technical implementation of grid-connected gravity energy storage systems. Their study provides valuable insights into the design and simulation of these systems, specifically demonstrating how optimized GESS can deliver stable power generation. They further suggest that such systems can function similarly to a controlled current source, offering enhanced flexibility for grid management.

What Is a Gravity Battery?

A gravity battery is an energy-storage system that uses elevation and gravity as part of its storage process. Electricity is used to raise water or a solid mass. When electricity is required, the system allows the water or mass to descend in a controlled manner and uses the resulting movement to generate electricity.
The energy stored is related to the mass and the vertical change in height. A larger mass or greater height can increase theoretical potential energy. However, the theoretical calculation alone does not determine the usable output. Engineers must also consider the capacity and efficiency of pumps, motors, generators, turbines, cables, pulleys, power converters, and control equipment.A gravity battery is therefore not simply a weight that can be lifted and dropped. It is an integrated mechanical and electrical system. It must control movement precisely, support the load safely, convert energy efficiently, and connect to the intended customer or grid. The term “battery” is used because the system stores energy for later use. Unlike a chemical battery, however, a gravity system stores energy through a change in the position of a mass or body of water. This makes it particularly relevant to stationary applications, where large structures and equipment can be installed at a suitable site.

Main Types of Gravity Storage

Water-Based Systems: Pumped-Storage Hydropower

Pumped-storage hydropower (PSH) stores energy by pumping water between reservoirs at different elevations. In a typical arrangement, one reservoir is higher than the other. During charging, electricity drives pumps that move water to the upper reservoir. During discharge, water flows downhill through a conduit and turns turbines connected to generators.
The process has four main stages:

1. Pumping water uphill: When electricity is available for storage, pumps move water from the lower reservoir to the upper reservoir.
2. Holding water: The upper reservoir retains the water until electricity is required.
3. Releasing water: Operators release the water through pipes or other water passages.
4. Generating electricity: The moving water turns turbines and generators before collecting in the lower reservoir.

PSH can support large-scale energy management. Its capacity and power output depend on the reservoir volume, elevation difference, equipment, and project design. It can be useful for moving energy across hours or other operating periods, subject to the plant’s configuration.

Its feasibility is strongly influenced by physical geography and environmental conditions. A project may need a suitable elevation difference, sufficient land, appropriate geological conditions, water resources, and a grid connection. Construction can involve major civil works and a lengthy development process. Reservoirs and associated infrastructure may alter land and water systems, so environmental assessment is important.

The water is generally circulated within the system, but the plant is not impact-free. Water management, evaporation, seepage, sediment, ecological conditions, and local water rights may matter. The project must also account for pumping and generation losses: the electricity returned is lower than the electricity used to pump water uphill.

Wind-Based Gravity Storage

Wind turbines may at times produce more electricity than can be used locally or transmitted at a reasonable value. If a gravity-storage system is available and has room to charge, some of that electricity can power pumps or lifting equipment.

A simplified sequence is: Wind turbines generate electricity.

Electricity that is available for storage is directed to the gravity-storage system.

Pumps or motors move water or a solid mass to a higher position.

Stored energy is held until required.

During lower wind generation or higher demand, the mass or water is lowered.

A turbine or motor-generator produces electricity for the grid or a customer.

This arrangement may shift some energy from a period of high wind output to a later period. It does not make wind itself predictable, and it cannot remove the need for forecasting, transmission, balancing resources, or other grid measures. Its value depends on storage capacity, losses, the charging schedule, discharge opportunities, and the cost of the project.

Co-location with a wind farm could reduce certain connection or land costs in some cases, but this must be assessed for the site. Wind farms may be in remote, hilly, or coastal areas, and not all such locations have the elevation, geology, or infrastructure required by a gravity-storage design.

Solar-Based Gravity Storage

Solar panels produce electricity when sunlight is available, with output affected by cloud cover, season, and daylight hours. A gravity-storage system can take some electricity during periods of solar surplus and release it later, such as during evening demand or when solar production is low.

The operating sequence is: Solar panels generate electricity.

Electricity not needed immediately is made available to the storage system.

A motor, winch, or pump raises the mass or moves water uphill.

The system holds the stored energy until a planned discharge period.

The mass is lowered or water is released.

A generator supplies electricity to the grid or a connected user.

This can improve the timing of energy supply, but it does not eliminate solar variability. It also does not guarantee that every project can supply electricity through a whole night or a particular number of days. Those outcomes depend on the storage capacity, power rating, operating schedule, and design.

Main Components

A gravity-storage system may contain some or all of the following:

A storage medium, such as water, concrete, rock, sand, or steel weights

An upper and lower reservoir, or a shaft, tower, slope, mine, or other supporting site

Pumps and water conduits in water-based systems

Motors, generators, turbines, winches, hoists, cables, pulleys, brakes, or lifting equipment

Foundations, supporting frames, retaining structures, and civil works

Power converters, transformers, switchgear, and grid-connection equipment

Sensors, communications, automation, and control systems

Safety systems for movement, pressure, overspeed, structural loading, and emergency shutdown

Inspection access and equipment for maintenance
The component selection depends on the architecture and the site. Not all systems use the same equipment, and a cost or performance figure from one design may not apply to another.

3. Research Methodology

This paper examines the following propositions:
Gravity storage may be useful for stationary energy-storage applications, including some applications that require energy to be shifted over longer periods.
Pumped-storage hydropower is a mature form of gravity storage, while solid-gravity systems represent a varied group of developing designs.
Combining multiple services may improve project value, if market rules and system operation allow those services to be delivered.
Long-lived civil infrastructure may reduce the need for frequent replacement of an entire system, but equipment still requires inspection, maintenance, and possible replacement.

Storage

After the water or solid mass reaches a higher elevation, it is held in place. Water remains in an upper reservoir, while a solid mass may be supported by a structure or retained by mechanical equipment and braking systems.
Stored energy should not automatically be described as having "zero leakage" or "no degradation." A raised mass may retain its gravitational potential energy while stationary, but the overall installation may have auxiliary electricity use, control-system requirements, mechanical wear, or other losses. The storage properties depend on the design and on how it is operated.

Discharging

When electricity is needed, water is released through a pipe or conduit to turn a turbine, or a solid mass is lowered under controlled conditions. The movement drives a turbine or a motor operating as a generator. Power electronics then condition the output for delivery to a local load or the electricity grid.
The descent must be controlled so that the system can meet operating requirements without exceeding the safe operating limits of its structure or machinery. Controls coordinate the mechanical equipment and electrical output.

Challenges and Limitations

The deployment of gravity storage can face technical, financial, environmental, and institutional challenges.

1. High initial capital cost: Large civil structures, reservoirs, shafts, towers, machinery, and grid connections can require substantial upfront investment.
2. Geographical constraints: Pumped hydro generally requires appropriate elevation and water conditions. Solid-gravity systems also need suitable structures, space, and engineering conditions.
3. Low energy density by mass and volume: A large mass or volume may be needed to store substantial energy, potentially requiring significant land or structural capacity.
4. Grid-integration requirements: The project needs suitable interconnection equipment and must meet applicable grid codes, dispatch rules, and protection requirements.
5. Response and operating limits: The response time depends on design, equipment, and operating state. Claims that all gravity systems are either slow or instant are too broad; each design should be assessed for its actual capabilities.
6. Supply-chain needs: Specialized cables, motors, winches, generators, turbines, steel, concrete, and construction equipment may affect cost and schedule.
7. Environmental effects: Reservoirs, excavation, land use, construction traffic, and material production can affect ecosystems and communities.

Mechanical wear: Moving equipment is subject to wear. Cables, brakes, pulleys, bearings, turbines, and pumps require inspection and maintenance.
Round-trip losses: Energy is lost during pumping or lifting, conversion, electrical conditioning, and discharge. Overall efficiency depends on the full system.

Permitting and land rights: Environmental approvals, water rights, land acquisition, construction permits, and community consultation can lengthen development.

- Revenue uncertainty: Electricity prices and market rules can change. A project that depends on an assumed price spread may not achieve its expected income.

Technology and project risk: Newer designs may lack long operating records. Developers, lenders, and insurers may require additional performance evidence.

Safety and emergency planning: Projects require risk assessment for structural loads, moving masses, pressure systems, flooding where relevant, equipment failure, and worker access.

Decommissioning and site restoration: End-of-life planning should consider the removal or reuse of equipment and the restoration or continued use of the site.

Environmental Considerations

The environmental case for gravity storage should be evaluated across the project lifecycle. A system that does not use battery-cell chemistry may avoid certain mining and chemical-handling issues associated with some batteries, but it still uses materials and infrastructure.

Water-based projects may alter local waterways, reservoir areas, habitats, and land use. Their environmental assessment should consider water availability, water quality, aquatic and terrestrial ecosystems, land acquisition, and local communities.

Solid-gravity projects may use concrete, steel, rock, or other materials. Mining, production, and transport of these materials can cause emissions and other impacts. A design using recycled materials may reduce some impacts, but the quantity and quality of material available must be verified.

A potentially long service life can spread the impacts of construction over more years of operation, provided that the project performs as planned and is maintained effectively. Reuse of an existing mine or industrial site may offer benefits in certain circumstances, but mines may have ground-stability, access, contamination, or water-management issues.

Environmental claims should therefore be based on lifecycle assessment, including construction, operation, maintenance, component replacement, and decommissioning. A project should not be described as “zero impact,” “completely green,” or “free of hazardous materials” without evidence specific to its design and site.

Commerce and Business Analysis

Macroeconomic Perspective

At the national or regional level, energy storage may help manage the timing of electricity supply and demand. If storage can make renewable electricity available at a more useful time, it may contribute to more efficient use of generation assets. The scale of that contribution depends on the electricity system and cannot be assumed for every project.

Levelized Cost of Storage

The levelized cost of storage (LCOS) is one way to compare the lifetime cost of storing and delivering electricity. A calculation generally relates costs over a project’s life to the amount of energy delivered, with assumptions about investment, financing, operating expenses, efficiency, utilization, component life, and decommissioning.

A long project life may improve the cost per unit of delivered energy if the installation is used sufficiently and maintenance costs remain within expectations. However, long life alone does not prove that a system has the lowest LCOS. The result must be calculated using transparent assumptions and compared with alternative technologies or infrastructure.

Renewable-Energy Curtailment

Curtailment occurs when renewable electricity that could otherwise have been generated or delivered is reduced because of system constraints, demand conditions, or other factors. Storage may absorb some electricity that would otherwise have limited value and return it later. The economic benefit depends on how much energy can be captured, the energy lost during storage, and the value of the later discharge.

Energy Security and Supply Chains

Some gravity-storage designs use materials and equipment that may be sourced from established construction and industrial supply chains. Local sourcing could contribute to domestic

manufacturing and construction activity, but the actual supply chain may still include imported equipment, components, or specialized technology.

Storage can also contribute to energy-system resilience by providing electricity at a different time from when it was generated. It does not, by itself, guarantee energy independence or eliminate reliance on fuel, imported equipment, or transmission infrastructure.

Business Perspective

For a private developer, utility, industrial customer, or public authority, a gravity-storage system is an infrastructure investment. The business case must estimate costs and revenues over the expected project life.

Capital Expenditure (CAPEX)

CAPEX may include:

Feasibility studies, engineering, and project development
Land acquisition or site preparation
Excavation, reservoirs, shafts, towers, foundations, or other civil works
Water systems or mechanical lifting equipment
Motors, generators, turbines, cables, and control systems
Transformers, power electronics, and grid interconnection
Permitting, construction management, and commissioning

Cost estimates should include contingency for construction, land, schedule, and technology risks. Early estimates may differ considerably from final project costs.

Operating Expenditure (OPEX)

OPEX may include:

Staff and routine operation
Inspection, maintenance, and repairs
Replacement of wear components
Electricity used for charging and auxiliary services
Insurance, land costs, communications, and regulatory compliance
Environmental monitoring and site management

OPEX should not be assumed to be negligible. A mechanical system can require periodic maintenance, and a water-based system may have additional water and environmental management needs.

Energy Arbitrage

Energy arbitrage is the practice of charging a storage system when electricity has a lower market value and discharging it when electricity has a higher value. A simplified sequence is:

Lower-value electricity → charging → storage → discharge at a higher-value time

The gross price difference is not the project's net profit. The operator must account for charging costs, round-trip losses, operating costs, market fees, taxes where applicable, and any restrictions on dispatch. Future electricity prices are also uncertain.

Peak Shaving

An industrial or commercial user may operate storage to reduce electricity demand during high-demand periods. Where tariffs include demand charges or time-dependent prices, lowering a customer's peak grid demand may reduce costs. Whether this service is attractive depends on the tariff structure, the customer's load profile, the system's power capacity, and the cost of maintaining reserved capacity.

Backup and Reliability

A storage system may be used as part of a facility's resilience plan. For an industrial site, data centre, or manufacturing plant, interruptions may cause financial losses. A storage installation can potentially provide backup or bridge power, but it must be designed for the required load, duration, response, and reliability. The customer must also compare it with generators, battery systems, grid improvements, and other resilience options.

Repurposing Mine and Industrial Assets

A disused mine shaft or industrial site may appear suitable for a gravity-storage project because it already contains infrastructure or a vertical space. Such a project could create a new commercial use for a site that might otherwise require closure or remediation.

This possibility needs careful study. Developers must assess the condition of the shaft or structure, ground stability, water ingress, contamination, access, ownership, equipment installation, worker safety, and grid connection. Reuse may reduce some development needs but should not be assumed to eliminate site costs or environmental liabilities.

Value Stacking

Value stacking means generating value from more than one service. Depending on local market arrangements and system design, a gravity-storage project might combine:

Energy Arbitrage

Peak shaving for a customer
Capacity or availability services
Renewable-energy shifting
Grid balancing or other network services
Backup power or resilience support

These revenue sources are not automatically available to every project. Some services may require particular technical performance or market participation. Others may compete for the same stored energy or capacity. A detailed operating strategy should test whether the services can be combined without compromising reliability or breaching market rules.

Employment and Local Economic Activity

Gravity-storage projects involve engineering, construction, electrical work, equipment supply, commissioning, and long-term operations. They may create work for civil and structural engineers, mechanical and electrical engineers, construction workers, crane operators, riggers, technicians, control-system specialists, and maintenance personnel.

The number and duration of jobs depend on project scale, local procurement, construction methods, and the operating model. Job-creation estimates should be based on project plans rather than general statements. Local benefits may be greater where the project uses local expertise and suppliers, but specialized components could still come from outside the region.

Financial Evaluation Methods

A gravity-storage project should be assessed under multiple scenarios rather than through a single optimistic forecast.

Net Present Value

Net present value (NPV) compares the present value of expected future cash flows with the initial investment. The calculation discounts future revenue and expenses to reflect the time value of money and investment risk. A positive NPV under stated assumptions suggests that the project meets the chosen discount-rate threshold, but it does not remove the uncertainty in the assumptions.

Internal Rate of Return

Internal rate of return (IRR) is the discount rate at which a project's NPV equals zero. It is commonly compared with an investor's required return. IRR should be interpreted alongside NPV and the underlying cash-flow assumptions, especially when project cash flows are irregular or uncertain.

Payback Period

The payback period estimates how long it takes for cumulative project cash flows to recover the initial investment. It is easy to understand but does not fully account for cash flows after payback or the time value of money. It should not be used as the only measure of project attractiveness.

Sensitivity and Risk Analysis

Financial analysis should test changes in:

Construction cost and schedule
Financing cost and interest rates
Charging and discharging prices
System utilization and availability
Round-trip efficiency
Maintenance and component replacement
Market participation and revenue eligibility
Land, environmental, and permitting costs

This helps identify which assumptions have the greatest effect on returns. It also allows decision-makers to compare a gravity project with other storage technologies, demand management, transmission upgrades, or generation investments.

Opportunities and Considerations for India

India's growing use of renewable generation makes system flexibility and storage important areas for planning. Gravity storage could be considered where a project has an appropriate site and a clear use case. It should not be assumed that the same architecture can be applied across every state or region.

Project assessment should consider:

- Site suitability: Elevation, geology, land availability, water resources, mine infrastructure, or other structures.
- Renewable-energy location: Whether a storage system can be located close to wind or solar generation, a transmission corridor, or a major electricity user.
- Grid requirements: Whether storage can address a specific local or system-wide need.
- Market and policy rules: How storage can purchase electricity, sell electricity, and receive payment for any grid services.
- Environmental review: Effects on water, land, ecosystems, and nearby communities.
- Project economics: Construction, financing, utilization, revenue, and operating assumptions.
- Local skills and supply chains: Availability of civil, electrical, mechanical, and maintenance expertise.
- Technology evidence: Performance data from the specific design or comparable projects.

India-specific opportunities should be studied through site-level and system-level analysis. A technically promising location may still lack an attractive market arrangement, while a strong market need may not have a suitable gravity-storage site.

Discussion

Gravity storage has an intuitively simple operating principle, but commercial decisions require a much wider analysis. The equation $E = mgh$ describes the theoretical potential energy of an elevated mass; it does not by itself establish the cost, efficiency, reliability, or revenue of a project.

The distinction between pumped hydro and solid-gravity designs is particularly important. Pumped hydro is a mature storage approach with experience in large-scale energy systems. Its principal limitations include site requirements, civil construction, water considerations, and permitting. Solid-gravity systems may offer different architectural options, including the possible use of shafts or industrial locations, but the engineering and commercial evidence varies among designs.

Claims about lifespan and degradation require careful wording. A mechanical storage concept may not exhibit the same electrochemical capacity fade as a battery cell, but the project still contains parts that wear, corrode, fatigue, or require maintenance. Similarly, a raised mass may remain at height, but the whole system may use auxiliary power and has operational and conversion losses. Safety also needs to be assessed through project-specific engineering rather than inferred from the absence of battery chemicals.

The commercial case is equally site-specific. A project could earn value through arbitrage, peak shaving, renewable integration, or other services, but those opportunities depend on the local market and technical design. Combining several services can improve the business case only where they are compatible and adequately compensated. A robust financial analysis should therefore use realistic utilization and price assumptions, test downside scenarios, and compare the project with alternatives.

Conclusion

Gravity Battery Energy Storage Systems store electricity by using it to raise water or a solid mass and later converting some of the resulting gravitational potential energy back into electricity. The concept is grounded in established physics, but practical systems require integrated civil, mechanical, electrical, and control engineering.

Pumped-storage hydropower is the mature water-based form of gravity storage. Solid-gravity systems represent a developing group of designs that use masses, towers, shafts, slopes, mine

infrastructure, or other arrangements. These approaches have different site requirements and levels of commercial evidence, so they should be evaluated separately.

Gravity storage may contribute to renewable-energy integration, electricity shifting, peak management, and selected backup or grid services. It also faces considerable challenges: high upfront cost, site dependence, structural and mechanical requirements, conversion losses, maintenance, environmental review, grid connection, and uncertain revenue. Its business performance depends on CAPEX, OPEX, utilization, market prices, financing, design life, and access to more than one value stream.

The technology should therefore be viewed as one option within a wider portfolio of storage and grid solutions. A well-designed project must demonstrate technical performance, safety, environmental acceptability, and a credible financial case for its specific location and intended use.

References

1. Cai, K., Han, Y., Xia, R., Wu, J., Wang, J., & Lund, P. D. (2024). Gravity energy storage: A review on system types, techno-economic assessment and integration with renewable energy. WIREs Energy and Environment, 13(6), e543. https://doi.org/10.1002/wene.543
2. Kavoosi, A., & Tarafdar Hagh, M. (2025). Solid gravity energy storage: Pioneering energy storage solution—A review. Journal of Energy Storage, 113, 115691. https://doi.org/10.1016/j.est.2025.115691
3. National Renewable Energy Laboratory. (2013). The value of energy storage for grid applications (NREL/TP-6A20-58465).
4. Tong, W., Lu, Z., Chen, W., et al. (2022). Solid gravity energy storage: A review. Journal of Energy Storage, 53, 105226. https://doi.org/10.1016/j.est.2022.105226
5. U.S. Department of Energy. (n.d.). Pumped-storage hydropower. Energy.gov.
6. Wang, X., Yang, H., Li, X., et al. (2025). Gravitational energy storage: Media taxonomy, efficiency factors, comparison and selection. Applied Energy, 395, 126233. https://doi.org/10.1016/j.apenergy.2025.126233
7. Amorim, M. L. M., et al. (2026). A systematic review of gravity energy storage. Energy Reports. https://www.mdpi.com/2673-4117/7/9/463
8. Kavoosi, A., et al. (2025). Review article: Solid gravity energy storage. Journal of Energy Storage. https://www.sciencedirect.com/science/article/abs/pii/S2352152X25004049
9. Ji, Y., et al. (2025). Research on the design and simulation of grid-connected gravity energy storage systems. Scientific Reports. https://www.nature.com/articles/s41598-025-32410-2